

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

RAIL CLAMP RPBM025
CBHV-LH-150-025-W08-RP
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Sheet Number:

Job Number:

Form Number:

229-105-41591PT

Company / Project Reference:

Date.:



Page.:

1 OF 1


Document Package No.:

Rev.:

Inventor Drawing



INSTALLATION SHIMS
(BY CUSTOMER)



FEATURE	CODE
Rail Clamp type	CBHV-LH
Holding force	150
Coefficient of friction	025
Wedge	W08
No power unit	RP

Example for ordering	CBHV-LH-150-025-W08-RP
----------------------	------------------------

TECHNICAL DATA

Nominal holding force (kN)	150
Standard release pressure (MPa)	13
Maximum operating pressure (Mpa)	14.45
Cylinder volume (full stroke) (cm ³)	323
Cylinder volume (working stroke) (cm ³)	285
Mounting holes	14 x Ø26
Mounting bolts	14 x M 24 CL 8.8
Approximate weight (kg)	610
Mechanism - horizontal float (mm)	±25
Mechanism - vertical float (mm)	±25
Hydraulic connection	-6 37° JIC
Shipping crate (L x W x H) (mm)	1100 x 900 x 950

NOMINAL SPECIFICATION

Spring set - Hydraulically released device.

Control voltage electrical junction box connection to be drilled to suit requirements by customer.

RAIL WIDTH (mm)	MINIMUM TROUGH WIDTH TW (mm)
61 - 95	270
96 - 120	300
121 - 150	325

NOTES

All figures are nominal figures only.

All dimensions are in millimeters.

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\29a8009-260c-4c7b-b176-e444fca47a00180000524268\HILLMAR\HILLMAR PRODUCTION\02 STORM BRAKES\0700-2107002001 CXHV-LH\SPC-SHT-CXHV-LH\08 CBHV-XX-XXX-025-RP\41591 CBHV-LH-150-025-W08-RP.idw