

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

RAIL CLAMP RPBM050
CBHV-LH-800-050-W08-RP
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Company / Project Reference:

Date.:

Page.:
1 OF 1



Sheet Number:

Job Number:


Form Number:
229-110-44087PT

Document Package No.: Rev.:

Inventor Drawing



INSTALLATION SHIMS
(BY CUSTOMER)



FEATURE	CODE
Rail Clamp type	CBHV-LH
Holding force	800
Coefficient of friction	050
Wedge	W08
No power unit	RP

Example for ordering	CBHV-LH-800-050-W08-RP
----------------------	------------------------

TECHNICAL DATA

Nominal holding force (kN)	800
Standard release pressure (MPa)	13.5
Maximum operating pressure (Mpa)	14.95
Cylinder volume (full stroke) (cm3)	934
Cylinder volume (working stroke) (cm3)	824
Mounting holes	14 x Ø39
Mounting bolts	14 x M 36 CL 10.9
Approximate weight (kg)	1430
Mechanism - horizontal float (mm)	±25
Mechanism - vertical float (mm)	±25
Hydraulic connection	-6 37° JIC
Shipping crate (L x W x H) (mm)	1200 x 1000 x 1250

NOMINAL SPECIFICATION

Spring set - Hydraulically released device.

Control voltage electrical junction box connection to be drilled to suit requirements by customer.

RAIL WIDTH (mm)	MINIMUM TROUGH WIDTH TW (mm)
71 - 95	315
96 - 119	350
120 - 135	360
136 - 150	380

NOTES

All figures are nominal figures only.

All dimensions are in millimeters.

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\22e68076-0944-4b08-adc9-24765753c888\0000524257\HILLMAR\HILLMAR PRODUCTION\02 STORM BRAKES\0700-2\07002001 CXHV-LHSPC-SHT-CXHV-LH07 CBHV-XX-XXX-050-RP-44087 CBHV-LH-800-050-W08-RP.idw