




Inventor Drawing



FEATURE	CODE
Rigid coupling	RKM
Coupling size (Hub OD)	360
Load side	LSH
Disc diameter (mm)	0900
Disc thickness (mm)	30
Maximum coupling torque (Nm)	29100

Example for ordering	RKM-360-LSH-0900-30-29100
-----------------------------	----------------------------------

TECHNICAL DATA

Disc model	SDBD-0900-30-360
Disc diameter (mm)	900
Hub bore size MIN. (mm)	100
D2 MAX. (mm)	160
Moment of inertia (kgm ²)	16.123
Mounting bolts	12 x M24
Bolt tightening torque (Nm)	710
MAX. coupling torque TkMAX (Nm)	29100
MAX. coupling speed (RPM)	1750
Weight (kg)	221

CUSTOMER SPECIFICATIONS

Load side
D2: _____ mm
M2: _____ mm
K2: _____ mm
R2: _____ mm
C2: _____ mm

NOTES

Coupling balancing grade ISO 1940-G6.3 is guaranteed for all coupling parts.

All figures are nominal figures only

All dimensions are in millimeters

Document Template #710-101-62058

**** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE ****

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)