

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

RAIL CLAMP LEBM025
CBHV-LH-400-025-LE-W05-150PR5
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Company / Project Reference:

Date.:

Page.:
1 OF 1

Sheet Number:

Job Number:



Form Number:

229-107-47511PT

Document Package No.:

Rev.:

Inventor Drawing



FEATURE	CODE
Rail Clamp type	CBHV-LH
Holding force	400
Coefficient of friction	025
Power unit	LE
Wedge	W05
Motor - pump	150PR5

Example for ordering	CBHV-LH-400-025-LE-W05-150PR5
----------------------	-------------------------------

TECHNICAL DATA	
Nominal holding force (kN)	400
Standard release pressure (MPa)	13.3
Maximum operating pressure (Mpa)	14.75
Cylinder volume (full stroke) (cm ³)	633
Cylinder volume (working stroke) (cm ³)	559
Release time (s)	2-3
Mounting holes	14 x Ø39
Mounting bolts	14 x M 36 CL 8.8
Approximate weight (kg)	1230
Mechanism - horizontal float (mm)	±25
Mechanism - vertical float (mm)	±25
Hydraulic power unit mounting position	Standard A or B
	Optional C or D
Shipping crate (L x W x H) (mm)	1400 x 1100 x 1100

NOMINAL SPECIFICATION

Spring set - Hydraulically released device.

Control voltage electrical junction box connection to be drilled to suit requirements by customer.

Manual release by integrally mounted hydraulic handpump.

RAIL WIDTH (mm)	MINIMUM TROUGH WIDTH TW (mm)
71 - 95	315
96 - 119	350
120 - 135	360
136 - 150	380

NOTES

All figures are nominal figures only.

All dimensions are in millimeters.

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\6faaf675-4984-40a2-97da-3ca9bda22c180000524232\HILLMAR\HILLMAR PRODUCTION\02 STORM BRAKES\0700-2107002001 CXHV-LH\SPC-SHT-CXHV-LH\06 CBHV-XX-XXX-025-LEW7511 CBHV-LH-400-025-LE-W05-150PR5.idw