

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

COUPLING RKM
RKM-120-LSH-0355-20-1050
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Company / Project Reference:

Date.:

Page.:
1 OF 1


Sheet Number:

Job Number:



Form Number:
429-660-49381PT

Document Package No.: Rev.:

Inventor Drawing



LOAD SIDE



FEATURE	CODE
Rigid coupling	RKM
Coupling size (Hub OD)	120
Load side	LSH
Disc diameter (mm)	0355
Disc thickness (mm)	20
Maximum coupling torque (Nm)	1050

Example for ordering	RKM-120-LSH-0355-20-1050
----------------------	--------------------------

TECHNICAL DATA

Disc model	SDBD-0355-20-120
Disc diameter (mm)	355
Hub bore size MIN. (mm)	40
D2 MAX. (mm)	50
Moment of inertia (kgm ²)	0.249
Mounting bolts	8 x M10
Bolt tightening torque (Nm)	49
MAX. coupling torque TkMAX (Nm)	1050
MAX. coupling speed (RPM)	4100
Weight (kg)	18

CUSTOMER SPECIFICATIONS

Load side
D2: _____ mm
M2: _____ mm
K2: _____ mm
R2: _____ mm
C2: _____ mm

NOTES

Coupling balancing grade ISO 1940-G6.3 is guaranteed for all coupling parts.

All figures are nominal figures only

All dimensions are in millimeters

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\349bb3-e10c-4cd0-aed8-26c1b3378000\528397\HILLMAR\HILLMAR PRODUCTION\04 THRUSTER DB\0700-4107004005 PKM-GKM-RKSM-RKX\SPC-SHT-PKM-GKM-RKSM-RKX\04 RKX\49381 RKM-120-LSH-0355-20-1050.dwg