

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

HYD PWR UNIT 20-SM
HPT20-SM-MB1V3-400PR12
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Company / Project Reference:

Date.:

Page.:

1 OF 1

Sheet Number:

Job Number:


Form Number:

129-523-73174PT

Document Package No.:

Rev.:

Inventor Drawing



FEATURE

CODE

Hydraulic power unit

HPT

Oil volume

20

Reservoir SS304 steel mill

SM

Manifold

MB1V3

Motor - pump

400PR12

Example for ordering

HPT20-SM-MB1V3-400PR12

TECHNICAL DATA

Motor size (kW)

4

Oil volume (L)

20

Maximum pressure (MPa)

20

Hydraulic fittings (oil supply) T1

-6 x 37° JIC

Mounting bolts

4 x M12

Mounting holes

4 x Ø14

Weight w/o oil (kg)

75

NOMINAL SPECIFICATION

Stainless steel reservoir.

Gear pump and high-pressure outlet filter.

Circuit manifold having check-valve, relief valve, normally open solenoid valve with manual override, pressure gauge with isolation valve, flow control, motor cut-out pressure switch, accumulator with flow control valve.

Control voltage electrical junction box connection to be drilled to suit requirements by customer.



For electrical motor junction box connection see motor specification sheet for details.

NOTES

Hillmar power units can be customized to suit customer's special requirements

All figures are nominal figures only

All dimensions are in millimeters



Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\c47c86-3d26-49bf-b426-e08595715305\80000519323\HILLMAR\HILLMAR PRODUCTION\01 HYD PWR UNIT\0700-107001004 HPT-SM\SPC-SHT-HPT-SM\HPT20-SM-MB1V3-400PR12.idw