

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

CABLE REEL DA-MCGBSR DA-GB12SD-01KVFO-MC08-08

SPECIFICATION SHEET

SLS & MKTG

ENGLISH

Sheet Number:

Job Number:

Form Number:

629-861-75933PT




Document Package No.: Rev.:

Company / Project Reference:

Date.:

Page.:

Inventor Drawing



FEATURE	CODE
Drive Assy Power Reel	DA
Gearbox Single Drive	GB12SD
Voltage	01KV
Fiber Optic	FO
Magnetic Copupling	MC08
Magnetic Coupling Torque Nm	08 (8)

Example for ordering	DA-GB12SD-01KVFO-MC08-08
----------------------	--------------------------

TECHNICAL DATA

Motor Size	2.2 kW
Spool Sizes Available	1.6m to 4.6m
Gearbox Hollow Shaft	76mm
Gearbox Drive Torque Nm	2000
Gearbox Max Overhang Load	15kN
Slipring Enclosure Design	01kV
Rotary Switch Ratio	RS
Drive Weight Excluding Spool	405kg
Spool Weight	Contract Specific
Mounting Holes	8 x Ø22
Mounting Bolts	8 x M20 GR10.9
Slipring Enclosure	SS304

NOTES

For Other Reel Types refer to one of the following sections:

Flat Cable Reel

Hose Reel

Control Reel

Vector drive Reel

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\c0400308-2d99-417b-8fde-023eba837f0d\80000529718\HILLMAR\HILLMAR PRODUCTION\06 CABLE REEL\CABLE REEL DA0700-607006002 DAPR-MCGBSR\SPC-SHT-DAPR-MCGBSR\75933 DA-GB12SD-01KVFO-MC08-08.dwg