

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

CABLE REEL VD DAVD GBSR DAVD-0750-GB50SD-01KV-140

SPECIFICATION SHEET

SLS & MKTG

ENGLISH

Sheet Number:

Job Number:

Form Number:

629-863-75958PT

Company / Project Reference:




Date.:

Page.:

Document Package No.:

Rev.:

Inventor Drawing



FEATURE	CODE
Drive Assy Vector Drive	DAVD
Vector Drive Motor Size	0750
Gearbox Single Drive	GB50SD
Voltage	01KV
Fiber Optic	Not available
Vector Drive Torque Nm	140

Example for ordering	DAVD-0750-GB50SD-01KV-140
----------------------	---------------------------

TECHNICAL DATA

Motor Size	7.5 kW
Spool Sizes Available	4.0m to 8.5m
Gearbox Hollow Shaft	90mm
Gearbox Drive Torque Nm	8000
Gearbox Max Overhang Load	75kN
Slipring Enclosure Design	01kV
Rotary Switch Ratio	RS
Drive Weight Excluding Spool	760kg
Spool Weight	Contract Specific
Mounting Holes	8 x Ø22
Mounting Bolts	8 x M20 GR10.9
Slipring Enclosure	SS304

NOTES

For Other Reel Types refer to one of the following sections:

Flat Cable Reel

Hose Reel

Control Reel

Vector drive Reel

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\8718diff-874f-4422-bec7-fec3dc6093080000529824\HILLMAR\HILLMAR PRODUCTION\06 CABLE REEL\CABLE REEL DAVD-0750-GB50SD-01KV-140.idw