

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

CABLE REEL VD DAVD GBSR DAVD-1500-GB90DD-0610KV-560

SPECIFICATION SHEET

SLS & MKTG

ENGLISH

Sheet Number:

Job Number:

Form Number:

629-864-75975PT

Company / Project Reference:




Date.:

Page.:

Document Package No.:

Rev.:

Inventor Drawing



FEATURE	CODE
Drive Assy Vector Drive	DAVD
Vector Drive Motor Size	1500
Gearbox Dual Drive	GB90DD
Voltage	0610KV
Fiber Optic	Not available
Vector Drive Torque Nm	560

Example for ordering	DAVD-1500-GB90DD-0610KV-560
----------------------	-----------------------------

TECHNICAL DATA

Motor Size	15 kW
Spool Sizes Available	6.5m to 8.5m
Gearbox Hollow Shaft	95mm
Gearbox Drive Torque Nm	20000
Gearbox Max Overhang Load	100kN
Slipping Enclosure Design	06-10KV
Rotary Switch Ratio	RS
Drive Weight Excluding Spool	1250kg
Spool Weight	Contract Specific
Mounting Holes	6 x Ø33
Mounting Bolts	6x M30 GR10.9
Slipping Enclosure	SS304

NOTES

For Other Reel Types refer to one of the following sections:

Flat Cable Reel

Hose Reel

Control Reel

Vector drive Reel

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\vaut_workspace\HILLMAR\HILLMAR PRODUCTION\06 CABLE REEL\CABLE REEL DA0700-607006005 DA-CRVD\SPC-SHT-DA-CRVD\75975 DAVD-1500-GB90DD-0610KV-560.idw