

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

RAIL CLAMP TSUD
CBHV-TSUD-060-050RP
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Company / Project Reference:

Date.:

Page.:
1 OF 1



Sheet Number:

Job Number:

Form Number:
229-102-78368PT

Document Package No.: Rev.:

Inventor Drawing



FEATURE	CODE
Rail Clamp Upside Down	CBHV-TSUD
Holding force	060
Coefficient of friction	050
No power unit	RP

Example for ordering	CBHV-TSUD-060-050RP
----------------------	---------------------

TECHNICAL DATA

Nominal holding force (kN)	60
Standard release pressure (MPa)	7,3
Maximum operating pressure (Mpa)	8,75
Cylinder volume (full stroke) (cm3)	158
Cylinder volume (working stroke) (cm3)	140
Mounting holes	14 x Ø22
Mounting bolts	14 x M 20 CL 8.8
Approximate weight (kg)	290
Mechanism - horizontal float (mm)	±25
Mechanism - vertical float (mm)	±25
Hydraulic connection	-6 37° JIC
Shipping crate (L x W x H) (mm)	1100 x 900 x 950

NOMINAL SPECIFICATION

Spring set - Hydraulically released device.

Control voltage electrical junction box connection to be drilled to suit requirements by customer.

RAIL WIDTH (mm)	MINIMUM TROUGH WIDTH TW (mm)
40 - 70	250
71 - 95	250
96 - 120	280

NOTES

All figures are nominal figures only.

All dimensions are in millimeters.

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\boda9f3-8a70-4fb2-8a49-1e21c0ec2540\8000052438\HILLMAR\HILLMAR PRODUCTION\02 STORM BRAKES\0700-2\07002014 CTHV-LHUD\SPC-SHT-C\THV-LHUD\78368 CBHV-TSUD-060-050RP.dwg