

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

CABLE REEL DLLS4 DLLS4-0600-100-DCOTJB DIVERTER SLS & MKTG ENGLISH

Company / Project Reference:

Date.:

Page.:
1 OF 1


Sheet Number:

Job Number:

Form Number:
629-836-78469PT

Document Package No.: Rev.:

Inventor Drawing





FEATURE	CODE
Diverter low speed 304 SS	DLLS4
Radius mm	0600
Roller Width mm	100
Direction Control	DC
Overtension	OT
Wired Junction Box	JB

Example for ordering	DLLS4-0600-100-DCOTJB
----------------------	-----------------------

TECHNICAL DATA

Mounting Holes	4 x $\varnothing 18$
Mounting Bolts	4 x M16 CL 8.8
Weight	60kg



NOMINAL SPECIFICATION

Optimized bend radius for long cable life.
Direction & slack sensor proxy switches.
Overtension proxy switches and adjustable overtensions in both directions.
Flat faced delrin rollers for flat cable support.

Stainless steel constructed diverter body.
Stainless steel shafts in rollers.
Corrosion resistant steel construction.
All stainless steel fasteners.
Junction box Nema4X for prewired limit switches mounted on to diverter.

NOTES

All figures are nominal figures only
All dimensions are in millimeters

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **
Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)